

# DécorBatten

## Installation Guide

### Building Codes

Décortech Panels must be fixed in accordance to AS/NZS 2785. Installation is to comply with the following: loadings code AS/NZS 1170.1, the requirements of NZS 4219; related building services installations must comply with clauses 2.22, 2.25 and 2.29.

### Wall Fixings

DécorBatten panels can be fixed to walls using a good construction adhesive.

Sika Nailbond BP adhesive is recommended.

Mechanical fixings can be used inconjunction with the adhesive.

Battens or studs at 600mm centers maximum, with fixing at 200mm centers maximum around perimeter and 400mm centers maximum through center area of the panel.

### Drop In Ceiling Tiles

DécorBatten drop in ceiling tiles are designed to fit into standard 24mm 2-way exposed suspended ceiling systems, including existing installations. Drop In Tiles are easily installed as well as easily removed allowing for easy access to services. Exposing the grid systems creates an attractive detail.

### Ceiling Fixing

Battens should be at 400mm centers maximum, with fixing at 200mm centers maximum around perimeter and 400mm centers maximum through center area of the panel. We recommend good quality construction adhesive combined with some form of mechanical fixing i.e. screws or panel pins.

Screws 6 or 8 gauge x 30mm long minimum, panel pins 30mm long minimum.

Sika Nailbond BP adhesive is recommended.

While every endeavour has been made to ensure that all information is accurate, it is intended to be used as a guideline only. We reserve the right to amend specifications without notice.

For further information regarding  
Décortech DécorBatten Panels please  
contact Décortech .

DECORTECH LTD  
Freephone: 0800 211 311  
Phone: +64 9 579 5726  
[www.decortech.co.nz](http://www.decortech.co.nz)

Masterspec section 5172D