



## DECORTECH FIRESAFE DECORPLY PLYWOOD

Décortech is leading the way in solutions for fire resistant plywood, decorative and acoustic panelling. Exclusive to Décortech, Firesafe Décorply Plywood meets a Group 1S in accordance with NZBC Clause 3.4(a) being a type 2 substrate – Décorply has been tested to EN13501-1:2007 as per MBIE guidance 30 March 2015.C/VM2 Amendment 4, Table 2.

Décortech Firesafe Décorply Plywood is a pre-finished panel with a hard-wearing UV cured coating that retains the look and beauty of natural wood. Our panels come prefinished preventing the need for additional onsite trades after installation reducing costs as well as potential onsite issues such as spills, overspray or damage. Décortech Firesafe Décorply is available in a range of custom finishes including Clear, Nude, Blonded, Whitewash, Ivory, Mineral Tint of Brown, Blackwood, Harvest, Walnut, London Grey, First Avenue, and Nordic.



For further information regarding Décortech Firesafe Decorply Plywood please contact Décortech. laminated glue lines between plywood layers, voids in the plywood layers are natural and can be seen on the panel edge. While all care is taken, when plywood is machined, cut or perforated, chip-out can occur making Holes, Slots & Grooves slightly imperfect.

Décortech Firesafe Décorply is a natural product which is constructed with

When coating is applied to the face & panel edges the porosity levels and uptake of the applied coating can differ due to colour differences in the underlying substrate and face veneer plywood

## Why Wood?

Décortech specialises in decorative, acoustic and fire retardant timber panels utilising the many benefits of wood, including its renewability, sustainability, energy efficiency, and natural elegance. Timber brings a modern and warm look to any space and our Décortech Firesafe Decorply Plywood is enhanced by our Décortech factory applied finishes range for a premium result every time.

## DECORTECH LTD

Freephone: 0800 211 311 Phone: +64 9 579 5726 www. decortech.co.nz

Masterspec section 5172D

